

SLink
Cable

3/8" S PE

SL 038S PE



This product used for mobile network and telecommunication equipment

Material and dimensions

Inner conductor	Copper Clad Aluminum wire	Ø 2.6 mm
Dielectric	Foam PE	Ø 6.7 mm
Outer conductor	Corrugated copper(helically)	Ø 9.1 mm
Jacket	PE, Flame Retardant Non Corrosive(FRNC)	Ø 10.2 mm
	Black, UV resistant, Halogen free	
Ink marking: metric length	RosenbergerSLink™_SL 038S_PE_50Ω_ _ _ _ _ (DD+MM +SS+YY+NNNNN)_ _ _ _ _ XXXXm	

Documents

UV resistance	UL 1581; IEC 60068-2-5
---------------	------------------------

Electrical Specification

Impedance	50 ± 1 Ω
Relative Velocity of Propagation	83%
Capacitance	81 pF/m
Inductance	0.195 µH/m
Maximum Operating Frequency	13.4 GHz
Cut-off Frequency	16.1 GHz
Peak Power Rating	11.9 kW
Insulation Resistance	≥ 10 GΩ x km
DC Breakdown Voltage	2500V
Jacket Spark Test Voltage	5000 Vrms
Inner Conductor DC-resistance	≤ 5.3 Ω/km
Outer Conductor DC-resistance	≤ 4.95 Ω/km

Environmental Specification

Installation Temperature	-25°C to +60°C
Operating Temperature	-40°C to +85°C
Storage Temperature	-70°C to +85°C
2011/65/EU (RoHS)	compliant

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

RF_35/05.10/6.0

SLink
Cable

3/8" S PE

SL 038S PE

Mechanical Specification

Tensile strength	600 N
Min. bending radius (single)	13 mm
Min. bending radius (repeated)	25 mm
Number of bends, minimum (typical)	20 (50)
Bending moment	2.0 Nm
Flat plate crush strength	15 N/mm
Recommended hanger spacing	0.6 m

Standard Conditions

Attenuation, Ambient Temperature	20°C
Average Power, Ambient Temperature	40°C
Average Power, Inner Conductor Temperature	100°C

Return Loss

Return loss(Band A)	≤ -26dB 800 to 1000MHz
Return loss(Band B)	≤ -24dB 1700 to 1900MHz
Return loss(Band C)	≤ -24dB 1900 to 2200MHz
Return loss(Band D)	≤ -24dB 2200 to 2500MHz
Return loss(Band E)	≤ -24dB 2500 to 3000MHz

Intermodulation (3rd order, 2 x 20W) £ -117dBm @ 910MHz or 1800MHz (static and dynamic)

Attenuation

Frequency (MHz)	Attenuation (dB/100m)	Average Power (KW)
100	4.16	2.00
200	5.96	1.34
300	7.39	1.15
400	8.61	1.14
450	8.73	1.13
800	12.1	0.82
900	12.7	0.78
1000	13.4	0.74
1800	18.4	0.54
2000	19.5	0.51
2200	20.5	0.48
2500	22.1	0.45
2700	24.3	0.41
3000	24.7	0.40

Maximum attenuation value shall be 105% of the nominal attenuation value
Other frequencies on request

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Check	Approved	Date	Rev.	Engineering change number	Name	Date
Feifei	13/12/11				f1	16-m001	WG.Z	17/11/16
Rosenberger Hochfrequenztechnik GmbH & Co. KG, Germany Tel.: +49 8684 18-0 Fax: +49 8684 18-499 www.rosenberger.de email: info@rosenberger.de						Rosenberger Asia Pacific Electronic Co., Ltd., China Tel.: +86 10 80481995 Fax: +86 10 80497052 www.rosenbergerap.com email:info@rosenbergerap.com		Page 2 / 2

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

RF_35/05.10/6.0